


Revised 1/91

Material Safety Data Sheet



BRAND NAME
Collodion

SYNONYMS
Lacquer, Varnish

Note: Blank spaces are not permitted. If any item is not applicable or no information is available, the space must be marked to indicate that.

Section I

Manufacturer / Preparer Maridon Corporation 3953 SW Bruner Terrace Palm City, FL 34990	Emergency Telephone Number	800-535-5053
	Telephone Number for Information	407-286-8951
	Date Prepared	January, 1991
	Signature of Preparer (optional)	

Section II - Hazardous Ingredients / Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
Ethyl Ether CAS # 60-29-7	400 ppm	400 ppm		70%
Ethyl Alcohol CAS # 64-17-5	1000 ppm	1000 ppm		

Section III - Physical / Chemical Characteristics

Boiling Point	94.°F	Specific Gravity (H ₂ O = 1)	0.758
Vapor Pressure (mm Hg)	Unk	Melting Point	Unk
Vapor Density (AIR = 1)	>1	Evaporation Rate (Butyl Acetate = 1)	Unk

Solubility in Water
soluble/ partially soluble

Appearance and Odor
clear to slight haze; solvent odor

Section IV - Fire and Explosion Hazard Data

NFPA Rating: 4

Flash Point (Method Used)	-49°F	Flammable Limits	Unk	LEL	UEL
---------------------------	--------------	------------------	------------	-----	-----

Extinguishing Media
water fog; foam; CO₂; dry chemical

Special Fire Fighting Procedures

Wear full protective equipment including a self-contained breathing apparatus.

Unusual Fire and Explosion Hazards

heat or flame presents a fire and explosion hazard