

MATERIAL SAFETY DATA SHEET SPI #5004 SILVER PAINT THINNER FOR SPI# 5001/5002

Section 04 Reactivity Data

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

Section 05 Spill, Leak And Disposal Procedures

ACTION TO TAKE FOR SPILLS:
ABSORB WITH ABSORBENT MATERIAL AND DISPOSE OF IN OSHA APPROVED FIREPROOF CONTAINER.
WASTE DISPOSAL METHOD:
CONSULT FEDERAL, STATE, AND LOCAL REGULATIONS.

Section 06 Health Hazard Data

THRESHOLD LIMIT VALUE: 450 PPM
EFFECTS OF OVEREXPOSURE TO COMPONENTS OF THIS PRODUCT MAY INCLUDE:
SKIN IRRITATION WITH DISCOMFORT OR RASH
EYE IRRITATION WITH DISCOMFORT, TEARING, OR BLURRING OR VISION
NONSPECIFIC DISCOMFORT, E.G., NAUSEA, HEADACHE OR WEAKNESS
IRRITATION OF THE UPPER RESPIRATORY PASSAGES

OTHER EFFECTS AND ADDITIONAL INFORMATION:

SKIN PERMEATION CAN OCCUR IN AMOUNTS CAPABLE OF PRODUCING EFFECTS OF SYSTEMIC TOXICITY.

Section 07 First Aid Procedures And Physician Notes

FIRST AID INSTRUCTIONS:
SKIN CONTACT: WASH SKIN WITH SOAP AND WATER.
EYE CONTACT: FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. CALL PHYSICIAN IMMEDIATELY.
INHALATION: REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN AND CALL PHYSICIAN.
INGESTION: CALL PHYSICIAN IMMEDIATELY.

Section 08 Special Handling Information

RESPIRATORY PROTECTION: NONE WITH NORMAL USE
VENTILATION: USE WITH ADEQUATE LOCAL VENTILATION
PROTECTIVE GLOVES: NONE WITH NORMAL USE
EYE PROTECTION: LABORATORY SAFETY GOGGLES

Section 09 Special Precautions And Additional Information

HANDLING AND STORING: DO NOT STORE NEAR HEAT OR OPEN FLAME OR SOURCE OF IGNITION, E.G. MOTORS, ETC. STORE PRODUCT IN COOL, DRY LOCATION.
OTHER: WASH HANDS THOROUGHLY AFTER HANDLING AND BEFORE EATING OR SMOKING. OBSERVE LABEL PRECAUTIONS.

Section 10 Hazardous Ingredients

TABLE WITH 5 COLUMNS: MATERIAL, CAS#, %WT OR VOL, TLV (PPM), VAPOR PRESSURE. ROWS: ETHYL ACETATE, ACETONE, TOLUENE, BUTYL ACETATE.